

KÄRCHER HD 10/25-4 S

The HD 10/25-4 S cold water high-pressure cleaner in an upright construction style impresses with EASY!Force high-pressure gun, pressure switch control and Servo Control.

The HD 10/25-4 S cold water high-pressure cleaner with three-phase drive offers a high level of convenience and the impressive power of 250 bar with a maximum flow volume of 1,000 l/h. Due to the upright construction style, the machine requires less space than conventional machines and is easier to manoeuvre, particularly around obstacles. This is also helped by the large, rubber-tyred wheels, which make the machine easy to transport, even on rough terrain. Accessories that are not being used can be stored in the separate nozzle compartment so that they do not get lost.

New innovations guarantee effortless operation and time-saving set-up and dismantling: While the EASY!Force high-pressure gun makes use of the recoil force of the high-pressure jet to reduce the holding force to zero, the EASY!Lock quick-release fasteners make handling five times faster than with conventional screw connections, without losing any robustness or longevity. The 10/25-4 S has been designed for daily use in harsh conditions. The cleaning agent-resistant brass cylinder head and stainless steel pistons with ceramic sleeves ensure a long service life.

Features:

Proven Kärcher quality

- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic pistons.
- Reinforced, unbreakable plastic chassis.

For increased safety

- Integrated electronics system for machine monitoring.
- Automatic switch-off in case of low voltage range or overvoltage.
- Switches off in case of leaks or phase failure.

Outstanding mobility

- Large rubber wheels for negotiating uneven surfaces, stairs and landings.
- Proven sack truck principle for easy, ergonomic transport.

Save energy and time: EASY!Force high-pressure gun and EASY!Lock quick-release fasteners

- At last – work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release fasteners: durable and robust. And five times faster than screw connectors.

Standard Features / Accessories

Pressure cut-off
4-pole, three-phase motor with air and water cooling
3-piston axial pump, With ceramic pistons
Integrated water fine filter
EASY!Force trigger gun
Spray gun with soft grip
Electronic motor protection with LED display
Oil level indicator
Servo Control
Rotatable spray lance, 1050 mm
Brass water inlet
Power nozzle
4-pole engine (low-speed machine)

Part no. 1.286-902.0

TECHNICAL SPECIFICATIONS

Connected load	9,2 kW
Detergent tank	6 l
Dimensions (L x W x H)	560 x 500 x 1090 mm
Frequency	50 Hz
Max. Water feed temperature	60 °C
Pressure	30-250/3-25 bar/MPa
Quantity of current phase	3 Ph
Voltage	400 V
Water flow rate	500-1000 l/h
Weight	62 kg

