

KÄRCHER CV 30/1

Professional cleaning demands high standards of engineering and quality.

Kärcher brush-type upright cleaners incorporate modern technology and unique product benefits that meet all the requirements of professional vacuuming, sweeping and maintenance. Everything is engineered to the quality you expect from Kärcher: No compromises have been made. A manual adjustment enables you to set the brush to the ideal height for the pile being cleaned, and if the brush becomes blocked for any reason, a patented centrifugal clutch will disengage the unit before any harm can be done.

Suction tube (ID 35 cone) for problem areas. Kärcher upright vacuum cleaners are equipped with a detachable suction tube for vacuuming upholstery and getting into awkward corners and other difficult-to-reach areas.

The replaceable brush roller is very simple to change (after mechanical wear of the brushes or to use a stronger brush roller with red bushes as an optional accessory). An automatic brush pressure release mechanism is activated when the unit is at a standstill to keep the brush in perfect shape and to avoid damage to the carpet.

Medium to large areas are cleaned quickly with the CV 30/1. For use in shops, showrooms, offices, ticket halls, hospitals, hotels, restaurants, nursing homes or private households, the working width of 300 mm cleans even large areas in no time. The metal sole plate ensures a long service life in tough professional applications.

Robust and durable. Twin joints between the brush head and body are designed to withstand the high flexing loads that occur in continuous-duty applications.

Standard Features / Accessories

Crevice tool and upholstery tool /
Detachable suction tube
Filter bag Fleece
Height-adjustable handle
Safety class II



Part no. 1.023-116.0

TECHNICAL SPECIFICATIONS

Dimensions (L x W x H)	320 x 310 x 1220 mm
Working width	300 mm
Motor rating	Max. 1150 W
Container capacity	5,5 l
Frequency	50-60 Hz
Weight	8,4 kg
Length of cord access.	12 m
Air flow rate	48 l/s
Sound pressure level	68 dB
Voltage	230-240 V
Inside dia standard	ID/35 mm
Vacuum	207/20,7 mbar/kPa