

## KÄRCHER NT 50/1 Tact Te

The Professional NT 50/1 Tact Te wet and dry vacuum cleaner with multiple features. These include a 50-litre container with adjustable push handle and drain hose as well as an integrated power outlet.

Fine dust, coarse dirt and liquids: our NT 50/1 Tact Te wet and dry vacuum cleaner is truly unstoppable. Its 50-litre bumpered container with metal castors and an oil-resistant drain hose as well as the height-adjustable push handle make it ideal for cleaning work spaces and machines in production facilities, workshops and on construction sites. It was designed for the most demanding customers in industry and construction who rely on professional machines and appreciate uninterrupted, dust-free working on a daily basis. This is ensured by the proven Tact filter cleaning system and the moisture-resistant PES flat pleated filter, among other things. An integrated power outlet with an automatic on/off switch makes working with power tools easier, while the new central rotary switch enables easy selection of suction settings, and the speed can be continuously adjusted with a separate knob. Extensive, newly developed accessories come as standard with this and can be easily stored in the integrated suction hose and accessory storage feature.

### Features:

#### *Adjustable, ergonomic push handle*

- Thanks to a quick lock, the adjustable push handle adapts to the size of the operator.
- The push handle can be easily folded away to save space when storing the machine.

#### *Oil-resistant drain hose*

- Oil-resistant, integrated drain hose for easy emptying of liquids.

#### *Wide floor nozzle with quickly exchangeable inserts*

- Floor nozzle with brush strip and squeegee inserts. Effortless switching between wet and dry vacuuming.

#### *Central rotary switch*

- Convenient switching via central rotary switch.

### Standard Features / Accessories

Automatic switch-off at max. filling quantity

Automatic on/off switch for power tools

Power tool connection adaptor

Antistatic preparation

Container material, plastic

Eco filter system

Filter cleaning, Tact filter cleaning system

Filter bag, fleece

Flat pleated filter, PES

Crevice nozzle

On-board power cable storage

Sturdy bumper

Push handle

Protection class, I

Steering roller stop

Drain hose (oil-resistant)

Suction tubes, stainless steel, 2 x 0.55 m

**Part no. 1.148-411.0**

### TECHNICAL SPECIFICATIONS

Air flow rate

74 l/s

Vacuum

254/25,4 mbar/kPa

Container capacity

50 l

Rated input power

1380 W

Standard nominal width

ID-35

Voltage

220-240 V

Frequency

50-60 Hz

Quantity

1 Ph

Sound pressure level

68 dBA

Weight without accessories

18,3 kg

Dimensions (L x W x H)

640 x 370 x 1045 mm

Container material

plastic

